



MUNKEBO



Controlled .....  
abrasive  
load to  
our belt  
conveyors


.....  
Our bucket  
elevators  
are simply  
made to  
last longer



CLEMCO

# Belt Conveyors and Bucket Elevators

# Belt Conveyors with controlled Abrasive Load for the long Run



*The V-positioned support rollers help to secure a controlled abrasive load, save energy and avoid spillage*


Correct designed belt conveyors will last for a very long period.

They are typically used in fixed installations for transportation of large volumes of abrasive media from easy accessible areas – for example in blast rooms.

The abrasive load onto the conveyor belt is controlled via the floor hopper arrangement and the support rollers. This design prevent overload and avoid spillage.

The length of a belt conveyor is suited to the individual application.

Main data for belt conveyor	
Length	3 m and up
Height	270 mm
Width	450 mm
Belt width	300 mm
Horizontal belt speed	0,6 m/s
Drive motor	1,5 kW
Gear ratio	1:20
Belt adjustm. range	500 mm





# From Top to Toe, high wear resistant Bucket Elevators



The rugged built bucket elevators are used where large volumes of abrasive media must be elevated from one fixed point to another – for example from a floor collection hopper up and into an abrasive cleaning unit.


The bucket elevator uses minimum power consumption compared to performance.

The height of a bucket elevator is suited to the individual application.

Main data for bucket elevator type MB-BE-2	
Depth	890 mm
Width	286 mm
Height	Max 12 mtr.
No. of buckets/mtr.	3
Vertical bucket speed	1 m/s
Max. performance	6 m <sup>3</sup> /h
Drive motor	2,2 kW
Gear ratio	1:22
Belt adjustm. range	140 mm

*The Munkebo bucket elevator takes over when the belt conveyor has delivered its part of used abrasive*





*The Munkebo Recovery System for fixed installations*

## You can mix & match Munkebo Recovery Systems

As one item of equipment will rarely make a complete system, all Munkebo units are designed to complement each other.



# MUNKEBO

**CLEMCO**

Munkebo Clemco A/S

Smedeloekken 5-7  
DK 5330 Munkebo

Tel. +45 65 97 43 80  
Fax +45 65 97 47 45

[www.munkebo.com](http://www.munkebo.com)  
[info@munkebo.com](mailto:info@munkebo.com)